

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 749 904 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
12.02.1997 Bulletin 1997/07

(51) Int. Cl.⁶: **B65B 61/18, B31B 1/84**

(43) Date of publication A2:
27.12.1996 Bulletin 1996/52

(21) Application number: 96115280.8

(22) Date of filing: 11.04.1994

(84) Designated Contracting States:
DE GB IT SE

(30) Priority: 12.04.1993 US 45347

(62) Application number of the earlier application in
accordance with Art. 76 EPC: **94302511.4**

(71) Applicant: **ELOPAK SYSTEMS AG**
CH-8152 Glattbrugg (CH)


(72) Inventors:

- **Owen, Barry Charles**
Southfield, Michigan 48076 (US)
- **Pape, Leslie**
Novi, Michigan 48375 (US)

(74) Representative: **Burrows, Anthony Gregory**
Business Centre West
Avenue One, Business Park
Letchworth Garden City Hertfordshire SG6 2HB
(GB)

(54) **Container for spout fitment applicator**

(57) A pour spout fitment applicator applies a flanged pour spout fitment 36 through an opening 20 in a carton top panel 22. The applicator includes a rotatable shaft 28 having an anvil 46 secured thereto, a vacuum cup 48 mounted on the distal end of the anvil 46, and a cam-controlled pivotable chute segment 40 for co-ordinating the supply of one fitment 36 at a time to the vacuum cup 48. A linkage-and-toggle system 54 serves to turn the anvil 46 and the cam 30 so as to insert the individual fitment 36 directly into the opening 20. While backed-up by the anvil 46, the flange 37 of the fitment 36 is sealed by an ultrasonic sealer 50 with horn 52 to the inner surface of the top panel 22 around the opening 20. The applicator operates transversely to the path of movement of a single line of cartons 18 along a conveyor 14. Two or more applicators may simultaneously apply fitments (36) to closely adjacent cartons (18) in the single line.



EP 0 749 904 A3




European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 96 11 5280

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	US-A-4 456 118 (KAUFFMAN ET AL.) * abstract; figures * ---	1,7,10, 13	B65B61/18 B31B1/84
A	US-A-4 512 136 (CHRISTINE) * the whole document * -----	1,7,10, 13	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B65B B31B B60C B29C
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 20 December 1996	Examiner Hagberg, A
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04C01)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 0 800 994 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
15.10.1997 Bulletin 1997/42

(51) Int Cl.⁶: B65B 61/18

(21) Application number: 97500059.7

(22) Date of filing: 26.03.1997

(84) Designated Contracting States:
AT BE DE DK ES FI FR GB GR IE IT NL PT SE

• Fite Sala, Mena
08130 Santa Perpetua de Mogoda (ES)

(30) Priority: 11.04.1996 ES 9600827

(74) Representative:
SUGRANES - VERDONCES - FERREGÜELA
Calle Provenza, 304
08008 Barcelona (ES)

(71) Applicant: VOLPAK, S.A.
E-08130 Santa Perpetua de Mogoda (ES)

(72) Inventors:
• Marti Roche, Enric
08017 Barcelona (ES)

(54) Process for the application of closing pieces for bags during their continuous process manufacturing

(57) This process is applicable to automatic packaging machines which include a continuous shaping device for bags made from a flexible sheet of thermoweldable material bent into a "U" shape to form two equal walls (1) facing each other. The process comprises: a phase of forming the bag bottom (3); a phase of welding (5) the upper end of the walls (1) over a short length; a

cutting phase (8,9) to form an incut (12) having an inclined portion (16) in the walls (1); a phase of removal of welded portions (11) defined by the incut; a phase of separation of walls (1); a phase of application of a closing device (15); a phase of securing the closing device (15); a phase of welding the closing device (15) to said inclined portions (16); and a phase of forming the side of the bag.




FIG. 1

EP 0 800 994 A1

Description

Technical field of the invention

The object of the invention is a process for the application of closing pieces for bags during the continuous-process manufacturing of same, applicable in general to automatic packaging machines whose structure has a built-in device for continuous-process forming of bag-shaped packaging, using a sheet of flexible thermoweldable material. More particularly, the process of the invention is applicable to automatic packaging machines for liquid food products such as fruit juices and granulated, ground or powdered foods.

Background of the invention

Known in the art are many embodiments of automatic packaging machines which essentially incorporate into their structures a device for continuous-process formation of bag-shaped packages and a filling device arranged longitudinally and operating synchronically in continuous process. Such bags are generally made from a sheet rolled onto a drum, composed for example of a plurality of layers of paper and thermoweldable plastic material, basically presenting an essentially quadrangular format and relatively low thickness. Within the overall set of operations which the continuous-process forming device implements, there is a first phase in which the sheet of flexible material adopts a general "U" shape, a plurality of successive phases of bag forming as such, in which the bottom and side sections are thermowelded and, once the bag has been filled by filling with the product it is to contain, the bag is closed by welding of its top side. Under these conditions, in order to gain access for consumption of the product contained in the bag users have to use a cutting tool to make an opening for pouring.

In those cases in which the product contained in the bag is consumed in doses over a period of time which can be comparatively long, the bag generally requires a closing piece to preserve said product from the action of the environment. Such closing pieces include, amongst others, screw-threaded and pressure-fitted caps, dispensing devices, opening pieces using a cut functioning as spout, etc. In all these cases, the closing piece includes at least a closing body fixed by means of welding or by any other means to the bag, generally at one of its vertices.

Until the present time, the application of said closing pieces to bags such as those described above was carried out manually or by using applicator devices; in either case, that is, with manual application of closing pieces and with the known embodiments of applicator mechanisms for such devices, the main disadvantage was that they had low production capacity, which increased the costs deriving from product packaging.

Explanation of the invention

In order to provide a solution for the above-mentioned disadvantages presented by the known embodiments of closing device applicators such as those described above, a process is made known hereby for the application of closing pieces for bags during the continuous-process manufacturing of same.

The process of the invention for the application of closing pieces is applicable to automatic packaging machines which have a continuous-process forming device for packages in the form of bags made from a sheet of flexible thermoweldable material, said bags being formed by bending the sheet into a "U" shape to form two equal side walls facing and running parallel to each other at a relatively short distance one from the other.

The process for application of closing pieces of the invention is characterized in that it includes the following phases:

- in a first phase, the lower longitudinal end of the facing walls is welded to form a bag bottom;
- in a second phase, the upper longitudinal ends of the facing walls are welded over a portion of relatively short length superimposed on one of the longitudinal ends of the bag bottom;
- in a third phase, two cuts are made in both facing walls starting at their top edges, one vertical cut and one inclined cut which extends as far as the lower edge of the vertical cut, leaving the welded portions of the upper longitudinal ends between the vertical and inclined cuts;
- in a fourth phase, said welded portions are removed from the upper longitudinal ends, forming on both facing walls a corresponding incut;
- in a fifth phase, the upper longitudinal ends are separated;
- in a sixth phase, a closing piece is fitted perpendicularly between the inclined portions of the upper longitudinal ends;
- in a seventh phase, the inclined portions of the upper longitudinal ends are welded onto relatively short portions on either side of the closing piece, fixing it into position;
- in an eighth phase, the inclined portions of the upper longitudinal ends are welded along their entire length to the closing piece; and
- in a ninth phase, the facing walls are welded by means of a vertical welding strip which links the equal ends of the upper longitudinal ends and bot-

tom to form closed bag lateral sides and leave the top side open.

According to another characteristic of the process of the invention for the application of closing pieces, the vertical and inclined cuts on both facing walls are made simultaneously by die-cutting.

According to another characteristic of the process of the invention for the application of closing pieces, the welded portions of the upper longitudinal ends are removed by suction.

According to another characteristic of the process of the invention for the application of closing pieces, the upper longitudinal ends are separated by means of a separator fitted between the two walls.

According to another characteristic of the process of the invention for the application of closing pieces, the fitting of the closing pieces perpendicularly between the inclined portions of the upper longitudinal ends is implemented by means of an inserting device.

According to another characteristic of the process of the invention for the application of closing pieces, the inserting device includes a positioning-loading mechanism and a rotary inserting mechanism.

According to another characteristic of the process of the invention for the application of closing pieces, the inserting device includes a positioning-loading mechanism and a linear inserting mechanism.

Brief description of the drawings

The drawing sheets of this specification show the process of the invention for application of closing pieces for bags during the continuous-process manufacturing of such bags. In said drawings:

Figure 1 is a schematic view of a first mode of embodiment of the process of the invention;

Figure 2 is a schematic view of the separation of the facing walls prior to fitting the closing piece between them, according to the process of the invention;

Figure 3 is a schematic view of the closing piece position fixing according to the process of the invention;

Figure 4 is a schematic view of the welding of the closing piece to the facing walls according to the process of the invention; and

Figure 5 is a schematic view of another mode of embodiment of the process of the invention.

Detailed description of the example of embodiment

The process of the invention for the application of closing pieces for bags during their continuous-process

manufacturing is shown schematically in Figure 1. For the purposes of achieving suitable clarity of outline, said Figure 1 does not show those known parts of a continuous-process forming device for packages in the form of bags, and which play a part in the forming of bags from a flexible sheet of thermoweldable material bent into a "U" shape. In this way, Figures 1 and 2 show how the bending of said flexible sheet of thermoweldable material forms two equal walls 1 facing each other, running parallel to and at a relatively short distance from each other.

In the first phase of the process of the invention, the lower longitudinal end 2 of the facing walls 1 are welded without breaks over a width corresponding to that of a bag, forming the bottom 3 of same which, in this example of embodiment, has a curved circumference outline; it is understood that said bottom 3 can be horizontal or can present any other type of curvature suited to each specific case of application.

Afterwards, in the second phase of the process of the invention, the upper longitudinal end 4 of the facing walls 1 is joined by means of a welded piece 5 superimposed upon one end, the back end 6, of the bottom 3.

Afterwards, in the third phase of the process of the invention, two cuts are made by die-cutting at the upper edge 7 of the upper longitudinal ends 4: a first vertical cut 8 which delimits one side edge bag portion; and a second inclined cut 9 which extends as far as the lower edge 10 of the vertical cut 8.

Afterwards, in the fourth phase of the process of the invention, and simultaneously with the above die-cutting operation, the welded portions 11 of the upper longitudinal ends 4 are removed by suction, preferably by means of a sucker, forming an incut 12 of general "V" shape in each facing wall 1.

Afterwards, in the fifth phase of the process of the invention, and as shown in Figures 1 and 2, the upper longitudinal ends 4 are separated by means of a separating device 13 fitted between them, which device, as shown schematically in Figure 2, separates the two upper longitudinal ends 4 symmetrically with respect to the theoretical main longitudinal axis of the sheet bent in a "U" shape.

Afterwards, in the sixth phase of the process of the invention, the closing piece 15 is placed by means of an inserting device 14 between the inclined portions 16 of the upper longitudinal ends 4. The inserting device 14 shown schematically is rotary and essentially consists of two arms 17 which can rotate in the direction marked \vec{G} around a pivot 18, where each arm 17 during its rotation transports a closing piece 15 from a loading-positioning device 19 to between the said inclined portions 16. At this point it should be stated that the closing piece 15 can adopt any configuration and closing arrangement suited to each case of application, while, specifically, the closing piece 15 has to be adapted to the product which the bag is to contain; the closing piece 15 can thus include a pressure-fitted or screw-threaded cap, a

metering device, etc. In this example of embodiment of the process of the invention, the closing piece 15 consists, as shown in Figures 1, 3 and 4, of a closing body 20 of elliptical cross section upon which there is a centrally mounted cylindrical extension 21 provided with a centred passage 22, said extension 21 being fittable with a closing piece, such as a pressure-fitted metering device, not shown.

Afterwards, in the seventh phase of the process of the invention, the inclined portions 16 of the upper longitudinal ends 4 are joined by two welded sections 23 to both sides of the closing piece 15, at a relatively short distance from it, as shown in Figure 3, in such a way that the position of the closing piece 15 is fixed.

Afterwards, in the eighth phase of the process of the invention, a welded section 24 is made to join the inclined portions 16 with the closing piece 15, said welded section 24 extending, as shown in Figures 1 and 4, from the upper edge 7 to the lower edge 10 of the vertical cut 8 made in the third phase of the process.

Afterwards, in the ninth phase of the process of the invention, the facing walls 1 are welded by means a vertical welded strip 25 which links the similar ends 6 of the bottom 3, 26 of the welded inclined portion 16 and 28 of the upper longitudinal ends 4, forming a closed bag side.

The application process for closing parts for bags during their continuous-process manufacturing shown schematically in Figure 5 differs from that described above only in as relates to the inserting device 14, for which reason, for the purposes of greater clarity of outline, Figure 2 does not include all those reference numbers pertaining to parts common to both modes of embodiment. This inserting device 14 comprises a loading-positioning mechanism 29 and a cylinder 30 arranged to form a certain angle with respect to the upper edge 7 of the longitudinal ends 4 of the facing walls 1. Moving lineally in the direction marked A, the cylinder 30 transports a closing piece 15 from the loading-positioning mechanism 29 to between the inclined portions 16 through a guiding body 31, while by making a movement B in the opposite direction to the previous one, the cylinder 30 is left ready to transport another closing piece 15 in the way described above.

Claims

1. A process for the application of closing pieces for bags during their continuous-process manufacturing, applicable to automatic packaging machines which have a continuous-process forming device for packages in the form of bags made from a sheet of flexible thermoweldable material, said bags being formed by bending the sheet into a "U" shape to form two equal side walls (1) facing and running parallel to each other at a relatively short distance one from the other, which is characterized in that it includes the following phases:
 - in a first phase, the lower longitudinal end (2) of the facing walls (1) is welded to form a bag bottom (3);
 - in a second phase, the upper longitudinal ends (4) of the facing walls (1) are welded over a portion (5) of relatively short length superimposed on one of the longitudinal ends (6) of the bag bottom (3);
 - in a third phase, two cuts are made in both facing walls (1) starting at their top edges (7), one vertical cut (8) and one inclined cut (9) which extends as far as the lower edge (10) of the vertical cut (8), leaving the welded portions (11) of the upper longitudinal ends (4) between the vertical (8) and inclined (9) cuts;
 - in a fourth phase, said welded portions (11) are removed from the upper longitudinal ends (4), forming on both facing walls (1) a corresponding incut (12);
 - in a fifth phase, the upper longitudinal ends (4) are separated;
 - in a sixth phase, a closing piece (15) is fitted perpendicularly between the inclined portions (16) of the upper longitudinal ends (4);
 - in a seventh phase, the inclined portions (16) of the upper longitudinal ends (4) are welded onto relatively short portions (23) on either side of the closing piece (15), fixing it into position;
 - in an eighth phase, the inclined portions (16) of the upper longitudinal ends (4) are welded (24) along their entire length to the closing piece (15); and
 - in a ninth phase, the facing walls (1) are welded by means of a vertical welding strip (25) which links the equal ends (28, 26, 6) of the upper longitudinal ends (4) and bottom (3) to form closed bag lateral sides and leave the top side open.
2. A process for the application of closing pieces as claimed in Claim 1, characterized in that the vertical (8) and inclined (9) cuts on both facing walls (1) are made simultaneously by die-cutting.
3. A process for the application of closing pieces as claimed in Claims 1 and 2, characterized in that the welded portions (11) of the upper longitudinal ends (4) are removed by suction.
4. A process for the application of closing pieces as claimed in Claims 1 to 3, characterized in that the upper longitudinal ends (4) are separated by means of a separator (13) fitted between the two walls (1).
5. A process for the application of closing pieces as claimed in Claims 1 to 4, characterized in that the fitting of the closing pieces (15) perpendicularly between the inclined portions (16) of the upper longitudinal ends (4) is implemented by means of an in-

serting device (14).

6. A process for the application of closing pieces as claimed in Claim 5, characterized in that the inserting device includes (14) a positioning-loading mechanism (19) and a rotary inserting mechanism (17, 18). 5
7. A process for the application of closing pieces as claimed in Claim 5, characterized in that the inserting device (14) includes a positioning-loading mechanism (29) and a linear inserting mechanism (30, 31). 10

15

20

25

30

35

40

45

50

55




FIG. 2




FIG. 3






FIG. 4







European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 97 50 0059

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	GB 2 241 487 A (EMZO S A I C) * page 6, line 12 - page 7, line 21; figures 1,4 *	1	B65B61/18
A	FR 2 715 636 A (COMEXO) * claim 1; figure 1 *	1	
A	US 4 512 136 A (CHRISTINE) * column 2, line 53 - column 4, line 4; figure 1 *	1,5,7	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B65B B65D
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 24 June 1997	Examiner Bridault, A
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone V : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1501 01/92 (P/M/C/D)